

Declaration of Conformity – Ref.No 44027

In compliance with the Construction Products Regulation and The Construction Products (Amendment etc.) (EU Exit) Regulations 2020.

1. Identification code of product-type	High-pressure decorative compact laminate EDS-LK																																																																				
2. Identification	EDS-LK: Duropal XTerior compact – single-sided lacquering / Duropal XTerior compact – double-sided lacquering																																																																				
3. Intended use	Compact laminate panels/sidings for exterior wall and ceiling finishes (including suspended ceilings)																																																																				
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch																																																																				
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt																																																																				
6. System of assessment and verification	System 4																																																																				
7. Assessment of performance	not relevant																																																																				
8. European Technical Assessment	not relevant																																																																				
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>EDS-LK</th> <th>EDS-LK</th> <th>EDS-LK</th> <th rowspan="2">Harmonised technical specification</th> </tr> <tr> <th>Thickness</th> <td>6 mm</td> <td>8 mm</td> <td>10–13 mm</td> </tr> </thead> <tbody> <tr> <td><i>Essential characteristics/main features</i></td> <td colspan="3"><i>Declared performance</i></td> <td rowspan="13">EN 438-7:2005</td> </tr> <tr> <td>Reaction to fire (Euroclass)</td> <td colspan="3">D-s2,d0</td> </tr> <tr> <td>Fire resistance</td> <td colspan="3">NPD</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="3">NPD</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="3">NPD</td> </tr> <tr> <td>Resistance to fixings (face)</td> <td>min. 2,000 N</td> <td>min. 3,000 N</td> <td>min. 4,000 N</td> </tr> <tr> <td>Resistance to fixings (edge)</td> <td colspan="3">NPD</td> </tr> <tr> <td>Direct airborne sound insulation</td> <td colspan="3">NPD</td> </tr> <tr> <td>Flexural strength</td> <td colspan="3">min. 80 MPa</td> </tr> <tr> <td>Bending modulus of elasticity</td> <td colspan="3">min. 9,000 MPa</td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="3">approx. 0.3 W/(mK)</td> </tr> <tr> <td>Thermal shock resistance</td> <td colspan="3">passed</td> </tr> <tr> <td>Durability – Resistance to moisture</td> <td colspan="3">passed</td> </tr> <tr> <td>Dichte</td> <td colspan="3">min. 1,350 kg/m³</td> </tr> </tbody> </table>			Identification code	EDS-LK	EDS-LK	EDS-LK	Harmonised technical specification	Thickness	6 mm	8 mm	10–13 mm	<i>Essential characteristics/main features</i>	<i>Declared performance</i>			EN 438-7:2005	Reaction to fire (Euroclass)	D-s2,d0			Fire resistance	NPD			Water vapour permeability (wet cup)	NPD			Water vapour permeability (dry cup)	NPD			Resistance to fixings (face)	min. 2,000 N	min. 3,000 N	min. 4,000 N	Resistance to fixings (edge)	NPD			Direct airborne sound insulation	NPD			Flexural strength	min. 80 MPa			Bending modulus of elasticity	min. 9,000 MPa			Thermal conductivity	approx. 0.3 W/(mK)			Thermal shock resistance	passed			Durability – Resistance to moisture	passed			Dichte	min. 1,350 kg/m ³		
Identification code	EDS-LK	EDS-LK	EDS-LK	Harmonised technical specification																																																																	
Thickness	6 mm	8 mm	10–13 mm																																																																		
<i>Essential characteristics/main features</i>	<i>Declared performance</i>			EN 438-7:2005																																																																	
Reaction to fire (Euroclass)	D-s2,d0																																																																				
Fire resistance	NPD																																																																				
Water vapour permeability (wet cup)	NPD																																																																				
Water vapour permeability (dry cup)	NPD																																																																				
Resistance to fixings (face)	min. 2,000 N	min. 3,000 N	min. 4,000 N																																																																		
Resistance to fixings (edge)	NPD																																																																				
Direct airborne sound insulation	NPD																																																																				
Flexural strength	min. 80 MPa																																																																				
Bending modulus of elasticity	min. 9,000 MPa																																																																				
Thermal conductivity	approx. 0.3 W/(mK)																																																																				
Thermal shock resistance	passed																																																																				
Durability – Resistance to moisture	passed																																																																				
Dichte	min. 1,350 kg/m ³																																																																				
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Conformity is issued under the sole responsibility of the manufacturer identified in point 4.																																																																					

Signed for and on behalf of the manufacturer by:

Date of issue: 2023-01-18

Diethard Singer
General Manager / Pfleiderer Leutkirch GmbH
(Document was created electronically and is therefore valid without signature!)

NPD: performance not defined