

Declaration of Performance (CE) – Ref.No 2260

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	ClassicBoard V100 Ä, DecoBoard V100Ä – 2260
2. Intended use	Boards for interior fitments (including furniture) for use in dry conditions
3. Manufacturer	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt
4. Authorised representative	not relevant
5. System of assessment and verification	System 4
6. Assessment of performance	not relevant
7. European Technical Assessment	not relevant

8. Declared performance

Thickness		> 8.9 mm to ≤ 13 mm	> 13 mm to ≤ 20 mm	> 13 mm to ≤ 20 mm	> 20 mm to ≤ 25 mm	> 20 mm to ≤ 25 mm	> 25 mm to ≤ 32 mm	> 32 mm to ≤ 40 mm	Harmonised technical specification	
Essential characteristics/main features	Unit	Declared performance								
Reaction to fire		E		NPD	E	NPD	E	NPD	EN 3986:2004 +A1:2015	
Water vapour permeability, wet cup μ		NPD								
Water vapour permeability, dry cup μ		NPD								
Class, formaldehyde release		E1 E05								
Release (Content), pentachlorophenol (PCP)	mg/kg	< 3								
Airborne sound insulation (surface mass)		NPD								
Sound Absorption frequency range 250 Hz to 500 Hz		NPD								
Sound Absorption frequency range 1000 Hz to 2000 Hz		NPD								
Thermal conductivity (density)		NPD								
Air permeability		NPD								
Internal bond	N/mm²	0.45			0.4		0.35	0.3	0.45	
Swelling in thickness, 24 h	%	17	14		13			12	14	
Internal bond after boil test		NPD								

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Date of issue: 2024-07-09

i. V. Claus Seemann
Head of productmanagement core materials
(Document was created electronically and is therefore valid without signature!)

NPD: performance not defined