



FESTOOL



Festool GmbH
Wertstraße 20
73240 Wendlingen

represented by:
Festool Deutschland GmbH
Wertstraße 20
73240 Wendlingen

Telephone: +49 (0)70 24/804-24010
E-mail: customerservice-de@festool.com

[festool.com](https://www.festool.com)

Pfleiderer Deutschland GmbH
Ingolstädter Str. 51
92318 Neumarkt

Tel.: +49 (0)91 81/28-480
E-mail: info@pfleiderer.com

[pfleiderer.com](https://www.pfleiderer.com)

Subject to changes and errors. All illustrations are non-binding.
Prepared for Festool GmbH, 73240 Wendlingen, 12/2023.

Discover all Festool apps – download now for free on Android and iOS:



With the **Work App**, you can adjust your connected Festool tools individually to your work conditions, register for warranty all-inclusive or view your performance data at any time. If something should go wrong with your tool, the Work app sends you the right solution via push notification directly to your smartphone. This ensures optimal work progress and perfect results adapted to your requirements.



With the **Order App** you can find Festool tools, suitable accessories or consumables, create your digital watch list and conveniently send it to your specialist dealer. With the heart icon, you can add or remove products from your watch list and then send them to the specialist dealer of your choice. This way, you always have your favourite products in view and can also order conveniently while on the go.



With the **How-to App**, you can have a personal video guide to your Festool tool to-hand at all times. Our Festool experts offer tips on Festool tool applications and suitable accessories in a practical video format. Videos are divided into individual sections so you don't have to watch the full video. This saves time and provides you with the right advice on the construction site or in the workshop, allowing you to continue working straightaway.

FESTOOL

Processing tips for decorative panels.

Convincing quality and aesthetics.
Projects are only truly successful if the result is convincing. When working with decorative panels, the interaction of Pfleiderer decorative panels with our high-quality power tools ensures the best results.

PFLEIDERER

Tools for the toughest demands

Effortless processing of decorative panels.

Work quickly and precisely with products and accessories from Festool.

Cordless plunge-cut saw TSC 55



- › Concentrated torque and up to twice as fast work progress with an increased saw blade service life.
- › The lithium-ion batteries and the brushless EC-TEC motor with maximum efficiency provide maximum cutting performance and exceptional durability.
- › Whether with a dust collection bag or an extractor with Bluetooth® automatic switch-on – the Festool extraction system ensures virtually dust-free work

Plunge-cut saw with scoring function TSV 60



- › The built-in scorer can be adjusted with precision and, together with the scoring saw blade, it guarantees consistently splinter-free cuts on both sides.
- › Whether it's on the construction site or in the workshop, even large panels can be cut with precision.
- › The innovative KickbackStop in the plunge-cut saw with scoring function protects your workpiece and minimises the risk of injury.

Diamond cutting system DSC-AG 125



- › Fast, precise cutting up to a cutting depth of 23 mm in combination with the Festool guide rail.
- › Safe to guide thanks to the guide table seated on rollers.
- › Clean and healthy working in conjunction with the perfectly matched Festool mobile dust extractors.

Cordless pendulum jigsaw CARVEX PSC 420



- › Fast, tool-free changing of tables, baseplates and saw blades.
- › Electronic switch-on/off on both sides, reachable in every grip position.
- › Ergonomically optimized design for maximum cutting performance, flawless maneuverability and working nearly dust-free.

Cordless drill TXS 18



- › With the integrated LED light, you can work precisely even in dark corners – continuous lighting, afterglow or LED off can be controlled via the adjusting wheel. The brightness and duration of the afterglow can also be personalised via the Work App.
- › Compactness combined with the compatibility of an 18 V battery. Ideally suited for all applications with up to 6 mm screws. All 18 volt lithium-ion battery packs fit on the TXS 18 (except for the Ergo battery pack).








Cordless mobile dust extractor CLEANTEC CTC MIDI I




- › Adjustable suction power in three levels.
- › Manual cleaning: With the manual main filter and filter bag dedusting, the suction power can be quickly and easily recovered when the filter or filter bag is clogged.
- › With four battery packs and the TCL 6 DUO rapid charger, work can be done in most cordless applications without interruptions.
- › Convenient and fast: The extractor switches on automatically via the Bluetooth® battery pack.

OUR RECOMMENDATION FOR OPTIMAL RESULTS.

Here you will find the right basic settings for processing Pfeleiderer decorative panels with your Festool products.

Decorative panels	Description	Application recommendation for our Festool products							
		Plunge-cut saw TS 55 / TSC 55 / TS 60				Plunge-cut saw with scoring function TSV 60			
		Saw blade	Plunge depth	Rotational rate	Remark	Saw blade	Plunge depth	Rotational rate	Remark
	Duropal XTerior compact F (single-sided lacquering; 8 mm) Compact high-pressure laminate for outdoor use in flame retardant quality according to EN 438-6:EDF / intensive decors according to EN 438-6:EGF. With uniform black-coloured core and single-sided decorative acrylic lacquer on the top side and decorative melamine resin surface on the reverse.	TF 52	15 mm	6	no scoring unit required				
	Duropal HPL Compact (white core; 12 mm) Compact high-pressure laminate in standard quality according to EN 438-9:BCS. With uniform white-coloured core and decorative melamine resin surface on both sides.	TF 52	20 mm	6	no scoring unit required, edge grinding with abrasive P 120				
	Duropal HPL Compact (black core; 12 mm) Compact high-pressure laminate in standard quality according to EN 438-4:CGS. With uniform black-coloured core and decorative melamine resin surface on both sides.	TF 52	20 mm	6	no scoring unit required, edge grinding with abrasive P 120				
	PrimeBoard XTreme Matt/SuperMatt P2 (19 mm) Melamine resin faced chipboard with high quality and innovative multi-layer coating made up of UV-curing acrylic coatings.	TF 52	26 mm	6	no scoring unit required, edge grinding with abrasive P 120				
	Duropal Element XTreme P2 (20.6 mm) HPL bonded board consisting of a particleboard type P2 to EN 312, surfaced on both sides with Duropal XTreme, an attractive supermatt surface material with an anti-fingerprint effect.					TF 52	32 mm	6	exact adjustment of the scoring unit is recommended, if needed, break edges with abrasive P 240
	Duropal Element XTreme plus P2 (20.6 mm) HPL bonded board consisting of a particleboard type P2 to EN 312, surfaced on both sides with Duropal XTreme plus, an attractive supermatt surface material with an anti-fingerprint effect, which is ideal for horizontal, heavily used surfaces.					TF 52 und Z 42 WZD	50 mm	6	perfect industrial quality thanks to the scoring unit
	Duropal flameprotect compact (12 mm) Non-combustible fire protection panel of primarily mineral constituents with uniform white-coloured core and decorative melamine resin surface on both sides in accordance with EN 438-4.					Z 4 DIA F	20 mm	1	slightly wavy cutting surface, but edging is still possible

DSC-AG 125				Pendulum jigsaw PSC 420				Drilling / Screwing	
Saw blade	Plunge depth	Rotational rate	Remark	Saw blade	Stroke	Rotational rate	Anmerkung		
				HM 90/3,3	3	6	sawing from the bottom	All Festool cordless drills are suitable for processing. No special settings are necessary. Our recommendation for screwing façade panels:  The FX Depth Stop Chuck (Order no. 769126) precisely screws the screw to the exact depth, ensuring the panel has a consistent play on the substructure (0.3 mm)	
				HM 90/3,3	3	6	sawing from the bottom		
				HM 90/3,3	0-3	6	sawing from the bottom		
				S 75/2,8	0-3	6	sawing from the top with splinter guard		
				S 75/2,8	3	6	sawing from the top with splinter guard		
TL D 125 Premium 1,8 mm	20 mm	6	An alternative to the plunge saw, achieving excellent cuts after scoring (2 mm deep). Alternatively, tape off the cutting surface.						